

M-G365PDC1/PDF1

IMU (Inertial Measurement Unit)

■ GENERAL DESCRIPTION

The M-G365PDC1/PDF1 is a small form factor inertial measurement unit (IMU) with 6 degrees of freedom: triaxial angular rates and linear accelerations, and provides high-stability and high-precision measurement capabilities with the use of high-precision compensation technology. A variety of calibration parameters are stored in memory of the IMU, and are automatically reflected in the measurement data being sent to the application after the power of the IMU is turned on. With general-purpose SPI/UART support for host communications, the M-G365PDC1/PDF1 reduces technical barriers for users to introduce inertial measurement and minimizes design resources to implement inertial movement analysis and control applications. The features of the IMU such as high stability, high precision, and small size make it easy to create and differentiate applications in various fields of industrial systems.

■ FEATURES


- Small Size, Lightweight : 24x24x10mm, 10grams
- Low-Noise, High-Stability
 - Bias Instability : 1.2 deg/h
 - Angular Random Walk : 0.08 deg/rt(hr)
- Initial Bias Error : 0.1 deg/s (1 σ) / 3mG (1 σ)
- 6 Degrees Of Freedom
 - Triple Gyroscopes : ± 450 deg/s,
 - Tri-Axis Accelerometer : ± 4 G (PDC0) / ± 10 G (PDF0)
- 16/32bit Data Resolution
- Digital Serial Interface : SPI / UART
- Calibrated Stability (Bias, Scale Factor, Axial Alignment)
- Data Output Rate : to 2k Sps
- External Trigger Input / External Counter Reset Input
- Delta Angle/Delta Velocity Output
- Attitude Output Accuracy : ± 0.2 deg
- Calibration Temperature Range : -40°C to $+85^{\circ}\text{C}$
- Operating Temperature Range : -40°C to $+85^{\circ}\text{C}$
- Single Voltage Supply : 3.3 V
- Low Power Consumption : 16mA (Typ.)

■ APPLICATIONS

- Antenna Platform Stabilization
- Camera Gimbals
- Navigation Systems
- Vibration Control and Stabilization
- Pointing and Tracking Systems
- Autonomous Vehicle



■ FUNCTIONAL BLOCK DIAGRAM



■ SENSOR SECTION SPECIFICATION

T_A=25°C, VCC=3.3V, angular rate=0 deg/s, ≤±1G, unless otherwise noted.

Parameter	Test Conditions / Comments	Min	Typ	Max	Unit	
GYRO SENSOR						
Sensitivity						
Dynamic Range		—	±450	—	deg/s	
Scale Factor	16bit	-0.2%	66	+0.2%	LSB/(deg/s)	
	32bit	-0.2%	66x(2 ¹⁶)	+0.2%		
Nonlinearity (Best fit straight line)	1 σ, <300 deg/s	—	0.05	—	% of FS	
	1 σ, >300 deg/s	—	0.2	—	% of FS	
Misalignment	1 σ, Axis-to-axis, Δ = 90° ideal	—	0.01	—	deg	
Bias						
Initial Error	1 σ, -40°C ≤ T _A ≤ +85°C	—	0.1	—	deg/s	
Repeatability	1 σ, turn-on to turn-on ^{†3}	—	0.01	—	deg/s	
Bias Instability	Average	—	1.2	—	deg/hr	
Angular Random Walk	Average	—	0.08	—	deg/√hr	
Linear Acceleration Effect	Average	—	0.005	—	(deg/s)/G	
Noise Density	f = 10 to 20 Hz	—	0.002	—	(deg/s)/√Hz, rms	
Frequency Property						
3 dB Bandwidth		—	472	—	Hz	
ACCELEROMETERS						
Sensitivity						
Dynamic Range	PDC1 PDF1	— —	±4 ±10	— —	G	
Scale Factor	PDC1 : 16bit PDF1 : 16bit PDC1 : 32bit PDF1 : 32bit	-0.1% -0.1% -0.1% -0.1%	6.25 2.5 6.25x(2 ¹⁶) 2.5x(2 ¹⁶)	+0.1% +0.1% +0.1% +0.1%	LSB/mG	
Nonlinearity (Best fit straight line)	PDC1 : 1 σ, <2G PDF1 : 1 σ, <5G	— —	0.1	—		% of FS
Misalignment	1 σ, Axis-to-axis, Δ = 90° ideal	—	0.01	—		deg
Bias						
Initial Error	1 σ, -40°C ≤ T _A ≤ +85°C	—	3	—	mG	
Repeatability	1 σ, turn-on to turn-on ^{†3}	—	3	—	mG	
Bias Instability	PDC1 : Average PDF1 : Average	— —	14 16	— —	μG	
Velocity Random Walk	PDC1 : Average PDF1 : Average	— —	0.02 0.033	— —	(m/sec)/√hr	
Noise Density	PDC1 : f = 10 to 20 Hz PDF1 : f = 10 to 20 Hz	— —	48 80	— —	μG/√Hz, rms	
Frequency Property						
3 dB Bandwidth		—	167	—	Hz	
ATTITUDE OUTPUT						
Dynamic Range	Inclination Mode Euler Mode ANG1:Roll ANG2:Pitch ANG3:Yaw ^{†4}	-80 -45 -180 -180	— — — —	+80 +45 +180 +180	deg	
Scale Factor	16bit	— —	0.00012207 0.00699411	— —		rad/LSB deg/LSB
Accuracy	1 σ, Static ^{†4} 1 σ, Dynamic ^{†5} (100dps, max)	— —	0.2 0.2	— —	deg	
TEMPERATURE SENSOR						
Scale Factor ^{†12}	Output = 2634(0x0A4A) @ +25°C	—	-0.0037918	—	°C/LSB	

- *1) This is a reference value used for internal temperature compensation. There is no guarantee that the value gives an absolute value of the internal temperature.
- *2) This is the temperature scale factor for the upper 16bit (**TEMP_HIGH**).
- *3) Turn-on to turn-on / Day by day, estimated variation during 5 consecutive days.
- *4) Yaw axis is not compensated for errors caused by drift.
- *5) Dynamic accuracy is based on measurement data that has been measured from a stationary state.

Note) The values in the specifications are based on the data calibrated at the factory. The values may change according to the way the product is used.


Note) The Typ values in the specifications are average values or 1σ values.

Note) Unless otherwise noted, the Max / Min values in the specifications are design values or Max / Min values at the factory tests.

RECOMMENDED OPERATING CONDITION

Parameter	Condition	Min	Typ	Max	Unit
VCC to GND		3.15	3.3	3.45	V
Digital Input Voltage to GND		GND	—	VCC	V
Digital Output Voltage to GND		-0.3	—	VCC +0.3	V
Calibration Temperature Range	Performance parameters are applicable	-40	—	85	°C
Operating Temperature Range		-40	—	85	°C

OUTLINE DIMENSIONS



Outline Dimensions (millimeters)

NOTICE:

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. This material or portions thereof may contain technology or the subject relating to strategic products under the control of the Foreign Exchange and Foreign Trade Law of Japan and may require an export license from the Ministry of Economy, Trade and Industry or other approval from another government agency.

All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective companies.

©Seiko Epson Corporation 2020, All rights reserved

SEIKO EPSON CORPORATION

DEVICE SALES & MARKETING DEPT.

29th Floor, JR Shinjuku Miraina Tower, 4-1-6 Shinjuku, Shinjuku-ku,
Tokyo, 160-8801, Japan
Phone: +81-3-6682-4322 FAX: +81-3-6682-5016

Revised date OCT, 2020 in Japan
Rev.20201007